



### GENERAL DESCRIPTION AND MATERIALS

- Half-mask in nonwoven polypropylene and polyester with exhalation valve
- Aluminium adjustable nose clip and PU foam total nose seal
- Wide fabric and rubber elastic straps
- Welded contour

### MAIN BENEFITS

- Electrostatic filter media,
- Exhalation valve: reduce breathing resistance and avoid fog and heat inside the mask,
- Complete face seal for a better water tightness and optimal comfort,
- Fabric and Spandex wide elastic strap with pull through adjustor.

### MAIN APPLICATION FIELDS

- For occasional use in a very dusty environment. Protections against FFP1, FFP2 + toxic solid and liquid aerosols, such as chromium, manganese, nickel, platinum, strychnine, metal dust and smoke, viruses and enzymes, asbestos (only for maintenance and servicing)
- Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork, welding, melting, metal cutting out, hospitals, laboratories, medical controls, pharmaceutical industry, toxic waste treatment, batteries making (Ni-Cad)
- **Do not use if oxygen concentration is below 19% in the environment.**

### PACKING

- Box of 10 pieces
- Parcel of 20 boxes

### CE STANDARD

This mask is identical to the PPE which is the subject of EU type-examination and has been certified under **UE Type-examination certificate #715526**



Delivered on the 30/08/2019 by **BSI (notified body n° 0086)**

**According to the EC standard EN149:2001+A1:2009**