



SAFETY JOGGER

PROFESSIONAL



Light

LOGAN O1

LOGANO1

Lightweight and breathable slip-on shoe with elastic laces

The LOGAN O1 occupational shoes offer ultimate comfort thanks to their lightweight, breathable design. They feature a stretchable upper and elastic laces for an unbeatable fit. Perfect for the logistics, medical, and catering industries.

| | |
|---------------|--|
| Upper | TPU, 3D-Mesh |
| Lining | Textile |
| Footbed | SJ foam footbed |
| Outsole | EVA/Rubber (NBR) |
| Category | O1 / SR, ESD, FO, HRO |
| Size range | EU 35-48 |
| Sample weight | 0.315 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2022+A1:2024 |



BLK



WHT



Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Stretchable upper

Super elastic and stretchable textile for improved comfort and fit.




Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

SAFETY JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

Industries:
Logistics, Medical, Catering

Environments:
Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---------|--|--------------|---|--------------|
| Upper | TPU, 3D-Mesh | | | |
| | Upper: permeability to water vapor | mg/cm²/h | 48.1 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm² | 384.8 | ≥ 15 |
| Lining | Textile | | | |
| | Lining: permeability to water vapor | mg/cm²/h | 48.1 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm² | 384.8 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | Dry 25600 cycles/Wet 12800 cycles | 25600/12800 |
| Outsole | EVA/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm³ | 118.6 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.56 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.58 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.20 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.28 | ≥ 0.22 |
| | Antistatic value | MegaOhm | 33.6 | 0.1 - 1000 |
| | ESD value | MegaOhm | 19 | 0.1 - 100 |
| | Heel energy absorption | J | 34 | ≥ 20 |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com